SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



English-US
Last Revision Date: June, 2025
Supersedes: April, 2025

Technical Data Sheet

3M™ Carry Handles 8350

Product Description

3M™ 8350 Carry Handles are durable plastic strips with a non-tacky center insert and adhesive coated at each end. It is easy to create a convenient looped handle when the ends are attached to both sides of a box or package. These handles are available in standard dimensions (see 'Available Sizes' below) or dimensions can be customized for your application. 8350 “CP” Carry Handles are custom-printed to provide additional branding opportunity for retail product, to add bar-codes for bundled packages, or for other purposes.

Product Features

- Reinforced tape for higher reliability
- Customer convenience - easier to carry bulky packages.
- Custom colors and graphics available for improved branding, promotional messages, or in-store security.
- Excellent adhesion to a variety of package surfaces.
- Easy to apply.
- Stores easily at checkout counters.
- Reduces packaging materials.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Adhesive Type		*Pressure-sensitive rubber resin.
Total Thickness	ASTM D3652	0.284 mm (11.2 mil)
Product Construction		3M™ Carry Handle: Standard white carry portion material. 3M™ Carry Handle CP: Custom printed or colored carry portion material. Available in custom backing.
Max Load Per Handle		22.7 kg (50 lb)

Attribute Name	Value
*Note	Requires no heat, moisture, or solvent activation prior to use.

Typical Performance Characteristics

Attribute Name	Test Method	Temperature	Value
180° Peel Adhesion	ASTM D3330	23 °C (73 °F)	80 N/100mm (73 oz/in) [1]
Tensile Strength	ASTM D3759		4525 N/100mm (258 lb/in)
Elongation at Break	ASTM D3759		16 %

[1] 300 mm/min (12 in/min)

Handling/Application Information

Application Examples

• Handling products, such as: small appliances, small electronics, toys, lawn, garden, houseware and hardware items and some industrial products.
• Combining products (multipacks, duo-pouches or bags).
• Providing special promotional messages or UPC codes.

Application Techniques

Recommended Surfaces
• Paperboard printed and unprinted
• Corrugated cardboard
• Polyethylene and polypropylene (strong shrink film/poly bags)
• Polyester film
• Polyvinyl chloride (PVC) film

Surfaces That Should Be Reviewed For Suitability
• Wax coated/siliconized surfaces
• Wet surfaces (moisture condensation)
• Cold surfaces (<50°F [10°C])
• Some lacquer coated board
• Rough textured surfaces on which tape surface contact is significantly reduced

Directions for Use

1. Select appropriate carry handle to meet package weight limit.
2. Remove a single handle from pad and apply one end to side of package. Press full length of adhesive tape leg firmly onto package side with hand pressure.
3. Lay handle across top of package using hand to form a snug loop; press full length of remaining adhesive tape leg firmly onto the opposite side with hand pressure.
4. Handles should be attached to the sides and the bottom of boxes.
5. Do not apply the majority of or the entire adhesive portion of the handle to top of box. Adhesive legs must be positioned on the package sides (vertical dimension) to insure application success.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 18 months from date of manufacture.

Available Sizes

Attribute Name	Value
Total Handle Length	584 mm (23 in)
Handle Width	35 mm (1.375 in)
Adhesive Length Per End	152 mm (6 in) [1]
Handle Dimensions	Custom dimensions available

[1] Dimensions on either side of center insert

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or

packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Specialties Division
3M Center, St. Paul, MN 55144-1000
www.3M.com/packaging

3M is a trademark of 3M Company.
©3M 2025 (6/25)