SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.

English-US

Last Revision Date: June, 2024

Supersedes: May, 2018

Technical Data Sheet

3M™ Loop Reclosable Fasteners EBL Landing Zone EBLV CLP-02083

Regulatory Info/SDS

Product Description

3M™ EBL Landing Zone EBLV provides industry proven softness and closure performance for hook and loop systems on disposable baby diapers and adult incontinence briefs. We offer generic and custom graphic options to enhance your brand and connect with consumers. Our loop is manufactured using a non-woven web bonded to a film layer, resulting in a distinct structured soft surface. 3M™ EBL Landing Zone EBLV is compatible with a variety of hook types.

Product Features

- Secure closure performance for reliability
- High loft construction helps make dependable closures fast and easy
- Continuous film backing for robust diaper line processing
- Can be unprinted or printed in custom and generic patterns
  - Commonly printed due to graphic clarity
- Improved product graphics help generate aesthetic appeal
- Long roll lengths to reduce roll changes and splicing

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Performance Characteristics

Attribute Name	Test Method	Value
Shear-Peel	TM 3740	1000[1] gf [1]
Dynamic Shear to Hook	TM 3749	5500[1] gf/25.4mm [1]

[1] Max Load, 13mm x 25.4mm

Attribute Name	Value
Note	[1]Tested with 3M hook through 3M Personal Care Application Engineers. Test methods are available through 3M Personal Care Application Engineers. Disclosure of additional physical properties can be made upon customer's request relating to specifics of customer's intended use.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 10 months from date of manufacture.

Ordering Information

For lead times and minimum order quantity, please contact your 3M Sales Representative.

Available Sizes

Attribute Name	Value
Packaging	Finished Roll Packaging (typical values – may vary by customer) https://multimedia.3m.com/mws/media/2069372O/image-114-jpg.jpg

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

Important Notice

Test methods are available through Personal Care Technical Service. Disclosure of additional physical properties can be made upon customer's request relating to specifics of customer's intended use. This 3M product is of a specialized nature and restricted by 3M for sale to specifically approved accounts. 3M may modify, limit, or cancel a product or product type. This product is not intended for resale except as a component to the purchaser's end product.

Customer Commitment

The 3M Personal Care Business is committed to providing customers with innovative, superior quality products and accompanying excellence in service and responsiveness that enable you to be successful in your business endeavors. In partnership with 3M customers, and using a long-standing industry leadership position, uncompromising integrity, local representation, and access to a wealth of 3M technologies, the highly motivated 3M global team will focus on solving your most challenging problems and provide innovated, value added, sustainable solutions that meet the unique needs of a variety of industries.

3M™ Industrial Specialties Division
3M Center, St. Paul, MN 55144-1000
www.3M.com