SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



English-US

Last Revision Date: September, 2024

Supersedes: June, 2024

Technical Data Sheet

3M™ Marine Adhesive/Sealant 5200 (Tan)

Product Details

Regulatory Info/SDS

Product Description

3M™ Marine Adhesive/Sealant 5200 (Tan) is a one-part polyurethane that chemically reacts with moisture to deliver strong, flexible bonds. It has excellent adhesion to wood gel coat and fiberglass. It forms a watertight, weather-resistant seal on joints and boat hardware, above and below the waterline. In addition, its flexibility allows for dissipation of stress caused by shock, vibration, swelling or shrinking.

Product Features

- Tough/flexible polyurethane polymer.
- Non-shrinking.
- One-part moisture cure.
- Long working time.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Density	11.1 lb/gal
Consistency	Medium Paste
Base	Polyurethane

Typical Physical Properties

Attribute Name	Value
Color	Tan
Solids Content by Weight	99 %
Product Construction	06501 - 10 fl. oz. cartridge (295 ml) 21450 - 5 gal. pail (18.93 L)
Approximate Coverage	36.6 lineal m (120 LF) [1]

[1] 10.5 oz. [310 mm Cartridge]; 1/8 in (3 mm) bead

Typical Cured Characteristics

Attribute Name	Test Method	Value
Shore A Hardness	ASTM C661	58

Typical Performance Characteristics

Overlap Shear Strength

Temperature: 23 °C (73 °F)

Substrate	Value
Teak	35.1 kg/cm² (499 lb/in²) [1]
Pine	48.1 kg/cm² (684 lb/in²) [1]
Oak	45.1 kg/cm² (642 lb/in²) [1]

Substrate	Value
Maple	49.6 kg/cm² (706 lb/in²) [1]
Fir	41.4 kg/cm² (589 lb/in²) [1]
Mahogany	41 kg/cm² (583 lb/in²) [1]
Steel	26.8 kg/cm² (381 lb/in²) [1]
Stainless Steel	14.3 kg/cm² (203 lb/in²) [1]
Aluminum	12.2 kg/cm² (173 lb/in²) [1]
Brass	12.7 kg/cm² (181 lb/in²) [1]
Bronze	14.3 kg/cm² (203 lb/in²) [1]
Copper	15 kg/cm² (214 lb/in²) [1]
Lead	5.2 kg/cm² (74 lb/in²) [1]
Zinc (Galvanized)	15 kg/cm² (213 lb/in²) [1]
Fiberglass	26.4 kg/cm² (376 lb/in²) [1]
Gelcoat	27.3 kg/cm² (388 lb/in²) [1]
Acrylic (PMMA)	11.9 kg/cm² (169 lb/in²) [1]
Nylon	8.7 kg/cm² (124 lb/in²) [1]
ABS	17.4 kg/cm² (248 lb/in²) [1]
Polypropylene (PP)	5.4 kg/cm² (77 lb/in²) [1]
Polyethylene (PE)	3.4 kg/cm² (48 lb/in²) [1]

[1] 25 mm (1 in) overlap specimens 2.4 mm (0.093 in) thick.
Cohesive – Adhesive/Sealant fails before adhesive/sealant releases from substrate. Desired failure mode.
Adhesive Failure – Adhesive/Sealant releases from substrate.

Attribute Name	Temperature	Value
Long Term Temperature Resistance		90 °C (190 °F) [1]
Minimum Long Term Temperature Resistance		-40 °C (-40 °F) [1]
Elongation		645 % [2]
Tensile Strength	23 °C (73 °F)	62.2 kg/cm² (885 lb/in²) [2]

[1] Long Term (day, weeks)

[2] A 3.2 mm (1/8 in) dumbbell specimen with a 3.2 mm (1/8 in) square cross section was tested at 51 mm/min (2 in/min)

Handling/Application Information

Directions for Use

Surface Preparation:
There are waxes, coatings, sealants, grease, oil and other contaminants used in the marine industry, making it very important to clean all surfaces to be bonded before applying 3M™ Marine Adhesive/Sealant 5200. Recommended procedures include cleaning with 3M™ General Purpose Adhesive Cleaner 08984.*

Application of Adhesive Sealant:
Abrading the surfaces with a 180 grit to 220 grit abrasive, and subsequently wiping off residue, will enhance the bond strength. Cut tip of the nozzle to desired bead size. Puncture seal inside the threaded nozzle end and screw on nozzle. If using a 10 fl. oz. cartridge, remove the bottom and seal and place the cartridge in a caulk gun. Apply 3M marine adhesive/sealant 5200 to the seam or part to be bonded.
Position parts. Tool material to desired appearance. Remove excess material with 3M general purpose adhesive cleaner 08984.*

Cure:

Cure	Relative Humidity	Temperature	Time	Cure Depth
Open Time	50%	70°F (21°C)	5 hours	N/A
Open Time	90%	90°F (32°C)	1.5 hours	N/A
Full Cure	50%	70°F (21°C)	2 days	1/8 inch (0.3175 cm)

Cleanup:
For cleaning 3M marine adhesive/sealant 5200 before it is cured, use a dry cloth to remove the majority of sealant, followed by a cloth damp with 3M general purpose adhesive cleaner 08984,* toluene or acetone. Cured 3M marine adhesive/sealant 5200 can be removed mechanically with a knife, razor blade, piano wire or sanding.
*Note: When using solvents, extinguish all ignition sources, including pilot lights, and follow the manufacturer's precautions and directions for use.

Limitations:
- Alcohol should not be used in preparation for bonding as it will stop the curing process.
- If painting on top of the sealant, always test to make sure there are no incompatibilities between the paint and the 3M marine adhesive/sealant 5200. Paints almost always crack on top of the sealant due to flexing in the joint.
- Heat resistance - Due to the decreased value in bond strength at elevated temperatures, we do not recommend use of this product above 190°F (88°C).
- Do not apply at temperatures below 40°F (4°C) or on frost covered surfaces. Do not apply at surface temperatures above 100°F (38°C).
- 3M marine adhesive/sealant 5200 is not recommended for use as a teak deck seam sealer. Extended exposure to chemicals (teak cleaners, oxalic acid, gasoline, strong solvents and other harsh chemicals) may cause permanent softening of the sealant.
- 3M™ Marine Adhesive/Sealant 5200 is not recommended for the installation of glass, polycarbonate or acrylic windows that are not also mechanically fastened with a system designed by the manufacturer. Inconsistent adhesion of these unprimed substrates, specific design of the window, and movement due to thermal expansion and flexing, may cause application failure. It is strongly recommended that the customer contact the window/port light/hatch manufacturer for recommendations on proper sealing procedures.
- When using 3M marine adhesive/sealant 5200 with metals, it may be necessary to prime the surface to achieve adequate adhesion and durability of the bond. 3M™ Scotch-Weld™ Structural Adhesive Primer EC-1945 B/A may be used for priming of most metals.

Application Examples

Typical bonding and sealing applications include:
- Fiberglass deck to fiberglass hull
- Wood to fiberglass
- Porthole frames
- Deck fittings
- Moldings
- Trunk joints
- Between struts and planking
- Stern joints and hull planking

Sealing of:
- Some plastics (test before assembly)
- Glass
- Metals

Structural bonding and sealing of:
- Wood
- Fiberglass
- Gel coat
- Primed metal

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original, unopened packaging, out of direct sunlight. Lower temperatures cause increased viscosity of a temporary nature. For best performance, use this product within 24 months from date of manufacture.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577

Automotive Disclaimer

Select Automotive Applications:
This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M and Scotch-Weld are trademarks of 3M.
©3M 2024 (9/24)