SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



English-US

Last Revision Date: September, 2024

Supersedes: August, 2024

Technical Data Sheet

3M™ PB924N High Temp High Strength Pressure Sensitive Non-Flammable Adhesive

Regulatory Info/SDS

Product Description

A Non-flammable high performance, high temperature resistant, tacky industrial grade spray adhesive for use in a wide variety of applications.

Product Features

- Bonds to a variety of substrates including decorative laminate, headliners, and soft foams.
- Typically used in construction, woodworking, specialty vehicle, RV, and manufactured housing.
- Non-Flammable solvent and propellant adhesive

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Base	Synthetic Elastomer
Density	10.1 lb/gal

Typical Physical Properties

Attribute Name	Value
Color	Translucent and Red
Solids Content by Weight	21.4 %
Spray Pattern	Lace
Dry Time	1 min [1]
Flammable Solvent	No
Bonding Range	1-60 min
Flammable Propellant	No
Coverage	39 ft² [2]
SCAQMD 1168 Compliant	No
VOC	<130 g/L
Hazardous Air Pollutants (HAPS)	55 — 65 % by weight

[1] Dry time will depend on ambient temperature, humidity and coverage applied.

[2] @ 27 g/m² (2.5 g/ft²) per Can

Typical Performance Characteristics

Attribute Name	Value
Shear Adhesion Failure Test - SAFT	116 °C (240 °F) [1]

[1] SAFT Shear Adhesion Failure Test with birch plywood, 25 mm (1 in) overlap, 100 g used, temperature start at 32 °C (90 °F) and ramped 5.5 °C (10 °F) every 10 min. until complete failure.

Cylinder Accessories

	3M™ Cylinder Spray Adhesive Applicators and Accessories	3M ID Numbers	UPC Numbers
Applicators	Cylinder Adhesive Applicator w/ 9501 tip	62-9880-9930-5	00-048011-61706-0
Hoses	Cylinder Adhesive 6' Hose	62-9880-0006-3	00-051115-25036-1
	Cylinder Adhesive 12' Hose	62-9880-0012-1	00-048011-61988-0
	Cylinder Adhesive 25' Hose	62-9880-0025-3	00-048011-61989-7
	Cylinder Adhesive 50' Hose	62-9880-0050-1	00-051115-25782-7

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original, unopened packaging, out of direct sunlight. Lower temperatures cause increased viscosity of a temporary nature. Higher temperatures reduce normal storage life. For best performance, use this product within 21 months from date of manufacture.

Available Sizes - Detailed

Container Size	3M Stock Number	UPC Number
Large Cylinder – 37 lbs. - clear	17-0000-0716-5	0-00-51131-28178-3
Large Cylinder – 37 lbs. - red	17-0000-0718-1	0-00-51131-28179-0
Intermediate Cylinder – 185.6 lbs. -	17-0000-0715-7	0-00-51131-28177-6
Intermediate Cylinder – 185.6 lbs. - red	17-0000-1374-2	0-00-51131-28435-9
Jumbo Cylinder – 371.7 lbs. - clear	17-0000-0719-9	0-00-51131-28180-6
Jumbo Cylinder – 371.7 lbs. - red	17-0000-0720-7	0-00-51131-28131-3

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577

Information

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

3M is a trademark of 3M Company.
©3M 2024 (9/24)