SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



Scotch® High Tack Box Sealing Tape 371+.

Last Revision Date: Oct, 2022

Supercedes: August, 2018

Download PDF

Ask a 3M expert

Product Description

Scotch® High Tack Box Sealing Tape 371+. is an industrial packaging tape used for box sealing, splicing, recouperage and other demanding packaging applications. This product has a conformable backing and aconsistent pressure sensitive hot melt
synthetic rubber adhesive system. Meets FDA requirements for indirect food contact.

Product Features

• Adheres instantly to a variety of surfaces.
• Edge tear and split resistance.
• Adheres well to recycled corrugate.
• Roll to roll consistency increases productivity for improved unit costs.
• Meets FDA requirements for indirect food contact.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values	Additional Information
Backing	Biaxially oriented polypropylene	
Adhesive Type	Pressure sensitive hot melt rubber-resin	
Color	Clear, Tan	
Backing Thickness (mm)	0.03 mm View	Test Method: ASTM D3652
Total Tape Thickness (mil)	2.1 mil View	

Test Method: ASTM D3652

Total Tape Thickness (mm)

0.053 mm

View

Test Method: ASTM D3652

Backing Thickness

1.2 mil

View

Test Method: ASTM D3652

Holding Power

8,000+ min

View

Test Method: ASTM D3654

Substrate: Fiberboard

Typical Performance Characteristics

Property
Values
Additional Information

180° Peel Adhesion

45 oz/in

View

Test Method: ASTM D3330

Notes: 12 in/min (300 mm/min)

180° Peel Adhesion

49.3 N/100mm

View

Test Method: ASTM D3330

Substrate: Stainless Steel

Tensile Strength

385 N/100mm (22 lb/in)

View

Test Method: ASTM D3759

Test Condition: Machine Direction

Tensile Strength

22 lb/in

View

Test Method: ASTM D3759

Test Condition: Machine Direction

Tensile Strength

385 N/100mm (22 lb/in)

View

Test Method: ASTM D3759

Test Condition: Cross Direction

Tensile Strength

22 lb/in

View

Test Method: ASTM D3759

Test Condition: Cross Direction

Elongation at Break (%)

160 %

View

Test Method: ASTM D3759

Available Sizes

Property	Values	Additional Information
Standard Roll Length	100, 914, 1500 m (109, 1000, 1641 yd)	
Standard Roll Length	109, 1000, 1641 yd	
Standard Width	48, 72 mm (1.9, 2.8 in)	
Standard Width	1.9, 2.8 in	
Core Size (ID)	76.2 mm (3 in)	

Core Size (ID)	3 in

Storage and Shelf Life

Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40 to 50% relative humidity are recommended.
To obtain best performance, use this product within 18 months from date of manufacture.

Industry Specifications

Meets FDA requirements for indirect food contact.

Trademarks

Scotch is a registered trademark of 3M.

Handling/Application Information

Application Techniques

An extensive line of application equipment including hand held manual dispensers and semi-automatic and fully automatic equipment is available. Application of Scotch® High Tack Box Sealing Tape 371+ is most easily accomplished at room temperature, however it can be applied at temperatures as low as 40°F(4.4°C). Once applied, Scotch® High Tack Box Sealing Tape 371+ performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

References

Property	Values
3m.com Product Page	https://www.3m.com/3M/en_US/p/d/b5005016009/
Safety Data Sheet SDS	https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=371+

Family Group

Link Tags:

371 371+

Products	Backing	Adhesive Type	Color	Backing Thickness (mm)	Total Tape Thickness (mm)
371	Biaxially oriented polypropylene	Pressure sensitive hot melt rubber-resin	Blue, clear, green, orange, red, tan, yellow, and white	0.03 mm	0.046 mm
371+	Biaxially oriented polypropylene	Pressure sensitive hot melt rubber-resin	Clear,Tan	0.03 mm	0.053 mm

ISO Statement

This Closure and Masking Systems Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.