SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



3M Science. Applied to Life.™

English-US

Last Revision Date: September, 2024

Supersedes: June, 2024

Technical Data Sheet

3M™ Scotch-Seal™ Metal Sealant 2084

Product Details

Regulatory Info/SDS

Product Features

• 3M™ Scotch-Seal™ Metal Sealant 2084 is a one-part aluminum colored sealant which air dries to a tough, flexible film that resists water, oils and fuel.
• Retains sealing properties after extended aging when painted.
• Can be used to bond and seal aluminum to glass; also adheres well to many other metals and woods. Painting after curing is recommended, especially if sealed area will be subjected to UV exposure.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Net Weight	7.7 — 8.1 lb/gal

Typical Mixed Physical Properties

Attribute Name	Value
Tack Free Time	5 min
Gap Fill	1 — 16 in

Typical Physical Properties

Attribute Name	Temperature	Value
Color		Aluminum
Solids Content by Weight		40 — 47 %
Viscosity	23 °C (73 °F)	500 — 2500 [1]
Viscosity	27 °C (80 °F)	7,000-22,500 cP [2]
Dry Time		1,440 min [3]
Solvent Resistance		Acetone
Coverage		1,500 LF/gal [4]
Flash Point		-18 °C (0 °F) [5]

[1] Brookfield Viscometer, RVF #6 sp. @ 4rpm
[2] Brookfield Viscometer, RVF #6 sp.
[3] Dry time will depend on ambient temperature, humidity and coverage applied.
[4] 3 mm (1/8 in) diameter wet bead
[5] Closed Cup

Typical Performance Characteristics

Temperature: 23 °C (73 °F)
Substrate: Canvas to Aluminum

Attribute Name	Value
180° Peel Adhesion	43.8 N/cm (400 oz/in) [1]

[1] 51 mm/min (2 in/min)

Handling/Application Information

Directions for Use

Surface Preparation: Best results are obtained on clean, dry surface. Oil, grease and other contaminants may be removed by wiping with a solvent such as isopropyl alcohol, MEK, acetone, or other locally compliant solvent.*

Application: Production dispensing is best achieved with pressure-flow equipment. Hand caulking guns may also be used.

Cleanup: Equipment and excess sealer may be cleaned with solvent such as isopropyl alcohol, MEK, acetone, or other locally compliant solvent.*

*Note: When using solvents for clean-up, extinguish all ignition sources and follow manufacturer's precautions and directions for use when handling such materials.

Application Equipment

Note: Appropriate application equipment can enhance adhesive performance. We suggest the following application equipment for the user's evaluation in light of the user's particular purpose and method of application.

Pump – 9 to 1 ratio double acting ball check type pump, 11.0 cu. inch per cycle with 41/4" air motor with single wiper follower plate. Packings, hoses and pail wiper must be compatible with acetone.
Hose – Nylon lined, 500 psi working pressure.
Reference Information
Material Temperature – 58°F (14°C)

Hose Assembly	Material Pressure psi	Output Lb./Min.	Material Pressure psi	Output Lb./Min.
Ten Foot Length 3/4 I.D. Hose	324	5.7	180	2.4
Twenty Foot Length 3/4 I.D. Hose	405	4.6	180	1.1
Twenty Foot Length 1/2 I.D. Hose	675	6.2	180	.48
Ten Foot Length 1/2 I.D. Hose	810	1.0	—	—

Note: Material pressure = operating air pressure x pump ratio.

Flow Gun – Tip seal type.
Manual Caulking Gun Filling – Kenmar® caulking gun loader with acetone resistant wiper; Graco® Model 225-975 gun loader with acetone resistant wiper; Pyles® Vaculoader.
Chemical Resistance Requirements – Synthetic materials in contact with 3M™ Scotch-Seal™ Metal Sealant 2084 must be resistant to acetone. Polysulfide, butyl, nylon and PTFE are compatible.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original, unopened packaging, out of direct sunlight. Lower temperatures cause increased viscosity of a temporary nature. For best performance, use this product within 15 months from date of manufacture.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577

Automotive Disclaimer

Select Automotive Applications:
This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

3M™ Industrial Adhesives and Tapes Division
3M Center, St. Paul, MN 55144-1000
3M.com/iatd

Kenmar is a registered trademark of Kenmar, Inc. Graco is a registered trademark of Graco, Inc.
Pyles is a registered trademark of Pyles, Inc.
3M and Scotch-Seal are trademarks of 3M.
©3M 2024 (9/24)