SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.



English-US

Last Revision Date: August, 2017

Technical Data Sheet

3M™ VentureClad™ Insulation Jacketing System 1577CW-WM

Product Details

Regulatory Info/SDS

Product Description

3M™ VentureClad™ Insulation Jacketing System is a zero permeability, all weather, multi-layered laminate coated with an aggressive cold weather acrylic adhesive. Superior resistance to weathering, fungi, UV and extreme environmental conditions. Designed for use as a vapor barrier for insulation cladding and jacketing applications. Available in both flat and embossed.

Product Features

- Superior adhesion in cold or hot and humid conditions temperatures.
- Bonds and seals at temperatures as cold as -10°F (-23°C).
- Zero permeability vapor barrier for insulation cladding and jacketing applications
- High puncture and tear resistant ensures longevity and durability
- Flexible and strong.
- Cuts and installs easily on-site, no special tools required.
- Available in multiple colors.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Test Method	Value
Color		White
Embossed		No
Puncture		147 N (33 lb)
Total Tape Thickness	ASTM D3652	0.18 mm (7 mil)
Water Vapor Transmission	ASTM E96	0 US Perms

Typical Performance Characteristics

Attribute Name	Test Method	Dwell Time	Temperature	Value
180° Peel Adhesion	ASTM D3330	1 min	22 °C (72 °F)	8.8 N/cm (80 oz/in) [1]
Tensile Strength				189 N/cm (108 lb/in)
Emittance				0.8

[1] 12 in/min (300 mm/min)

Attribute Name	Value
Long Term Temperature Resistance	120 °C (248 °F) [1]
Minimum Long Term Temperature Resistance	-40 °C (-40 °F) [1]

[1] Long Term (day, weeks)

Typical Environmental Characteristics

Chemical and Environmental Exposure

Acids	Acetic acid (all concentrations)	Resistant
	50% formic acid	Resistant
	10% hydrochloric acid	Resistant
	30% hydrochloric acid	Partially resistant
	10% and 35% hydrofluoric acid	Resistant
	10% nitric acid	Resistant
	65% and 100% nitric acid	Not resistant
	30% and 85% phosphoric acid	Resistant
	20% sulphuric acid	Partially resistant
	Sulphur dioxide gas, dry	Resistant
	80% and above sulphuric acid	Not resistant
Aldehydes	Acetaldehyde	Resistant
	Formaldehyde	Resistant
Aqueous Alkaline Solutions	Ammonium hydroxide	Not resistant
	Calcium hydroxide	Partially resistant
	Sodium hydroxide	Not resistant
Chlorinated Hydrocarbons	Carbon tetrachloride	Partially resistant
	Chlorinated biphenyls	Partially resistant
	Chloroform	Resistant
	Trichloroethylene	Resistant
Esters	Ethyl acetate	Resistant
Hydrocarbons	Aliphatic hydrocarbons	Resistant
	Benzene	Resistant
	Gasoline (petrol)	Resistant
	Mineral oils	Resistant
	Toluene	Resistant
	Xylene	Resistant
Miscellaneous Substances	Chlorine	Resistant
	Hydrogen peroxide	Resistant
	Oxygen	Resistant
	Water*	Resistant
Other Organic Solutions	Acetone	Resistant
	Diethyl ether	Resistant
	Nitrobenzene	Not resistant
	Phenol	Not resistant
Salt Solutions	Alkaline carbonates	Resistant
	Bichromates	Resistant
	Cyanides	Resistant
	Fluorides	Resistant

*Chemical resistance info based in part on third party test data of the product backing.

Environmental Resistance

Excellent

Certifications/Standards

Certifications

Product	1577CW-EMJ	1577CWE-EMJ	1577CW-WM	1577CW-WME
ASTM E84 Flame/Smoke Rating			25/45	25/45
UL723 Classified Flame/Smoke Rating (UL file #R10984)	25/25	25/25		
CAN/ULC S102 Classification Flame/Smoke Rating		15/20	25/25	
Meets FDA Compositional requirements for indirect food contact (21 CFR 175.105 and 21CFR175.125; FDA: Indirect Food Additives: Adhesives and Components of coatings)	X	X	X	X
Approved by Canadian Food Inspection Agency for use in food processing facilities as vapor barrier for insulation cladding and jacketing	X	X	X	X
Contains Mold Inhibiting Agents	X	X		
Passes ASTM C1338 Fungi Resistance Testing	X	X	X	X
U.S. Coast Guard Approval	X	X	X	X
IMO Resolution A653 (16)	X	X	X	X
IMO Resolution MSC61 (67) Annex 2 IMO Resolution MSC 61 (67) Annex 1 Part 2 and Annex 2	X	X	X	X
BS476 parts 6 & 7 Class "O"			X	X

Storage and Shelf Life

Store under normal conditions of 4° to 27°C (40° to 80°F) and 40 to 50% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 18 months from date of manufacture.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Specialties Division
3M Center, St. Paul, MN 55144-1000
www.3M.com

3M and VentureClad are trademarks of 3M Company.
©3M 2017 (8/17)