SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.

EVAC MINI SELF EVACUATION RESCUE KIT 20M

AFX209060(20)

The KStrong introduces the EVAC Mini, a compact and efficient descender/rescue device designed for use by a single user. It utilizes an automatic braking system to smoothly lower individuals at speeds of less than 2 meters per second. This device is particularly suitable for for Self evacuation or lowering of injured person.

Features

- Rescue from high level working platforms that require self evacuation or a simple rescue solution.
- Controlled descent speed: 2m/sec.
- Maximum Descent height: 250m. Refer UIM for more details.
- Descent load min. 30 kg - Descent load max. 141 kg
- Descent height max. 250 m
- Descent speed: <2m/sec
- Descent controllable via deflection points
- Automatic Brake System
- Must use 9.6mm Kernmantle Rope, EN 1891-A (EN 341, EN 1496), ANSI Z359.4:2013.
- Supplied Pre-assembled Kits c/w Anchor Strap & Rescue Triangle
- Can be supplied in 20m, 40m, 100m, 150m & 200m lengths

How To Use

Refer to User Instruction Manual

SCAN TO DOWNLOAD

Components

AFX209060	:	EVAC-MINI
Material	:	High Strength Aluminum Alloy & Steel Powder Coated Black
AFX200009.6	:	9.6mm Kernmantle Semi Static Rope 20m
AFC604020	:	Karabiners ANSI Aluminum 23 kN / 5000 lbs
AFA920015	:	Anchor Sling Webbing 1.5m, 23kN / 5000 lbs
AFX201035	:	Rescue Triangle Polyester & Aluminum Fittings 23kN
Bag	:	PVC



Total Kit Weight

4.677 kg

Relevant Standards

Conforms to EN 341:2011 – 1B & ANSI Z359.4:2013

