SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.

KSTRONG
UNRIVALED SAFETY.

BRUTE™ SERIES

BRUTE LEADING EDGE RETRACTABLE FALL ARREST BLOCKS WIRE ROPE

KStrong has developed a range of Retractable Fall Arrest Blocks in Galvanized Steel Rope specifically engineered for Leading Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.



Features and Benefits

- Swivel Anchorage Eye
- High Impact Load Bearing Polymer Casing
- Ergonomic Carry handle for ease of transportation
- 4.8mm Galvanised Steel Cable for added strength and safety
- Energy Absorber and Protective Cover
- Can be Used Horizontally
- Load Capacity 140 kgs for vertical use & 140 kgs for Horizontal use.
- Leading Edge Rated (R>0.5mm).
- MBS 15kN
- Temperature Range : -30°to +50°C
- QR code for ease of Identification and Service History
- ANSI Steel Swivel Snap Hook with Fall Indicator
- Can be supplied with Stainless Steel Cable and Stainless Steel Swivel Snap Hook on Request

Materials

- Polymer Casing
- 4.8mm Galvanized Steel Wire- MBS 15kN
- Steel ANSI Snap Hook - MBS 23kN
- Steel ANSI Karabiner - MBS 23kN

How To Use

- Refer to User Instruction Manual

SCAN TO DOWNLOAD



CE 0598

EN 360:2023
VG11 RFU 11.060
AS/NZS 1891.3 2020



AFS510003.5SE
Length: 3.5m
Weight: 2.34kg



AFS510006SE
Length: 6m
Weight: 3.34kg



AFS510010SE
Length: 10m
Weight: 4.62kg



AFS510015SE
Length: 15m
Weight: 6.00kg



AFS510020SE
Length: 20m
Weight: 6.40 kg