SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.

KSTRONG®
UNRIVALED SAFETY.

BRUTE™
SERIES

BRUTE TYPE 3 RETRACTABLE FALL ARREST WITH RETRIEVAL

KStrong has developed a range of Retractable Fall Arrest Blocks with an integrated Rescue Retrieval function that allows a person (after a fall) to be lifted up or down in a controlled manner, this eliminates the rescuer to descend to the person and reduces the amount of time involved to carry out the rescue.





CE 0598

EN 360:2023
EN 1496:2017 Class B
ATEX 2014/34/EU
AS/NZS 1891.3 2020

Ex II 2G

Features and Benefits

- Swivel Anchorage Eye
- High Impact Load Bearing Polymer Casing
- Ergonomic Carry Handle for ease of transportation
- Locking Pin to engage and release Fall Arrest and Rescue mode
- Integrated manual rescue mode function (hoisting and descending)
- Automatic Retractable Block
- Hydro Seepage System to allow water to be drained from block
- 4.5mm Galvanised Steel Cable for added strength and safety
- Snout reduces the locking of the cable when it is suddenly released
- Load Capacity 140kg
- MBS 15kN
- Temperature Range : -30°to +50°C
- QR code for ease of Identification and Service History
- ANSI Steel Swivel Snap Hook with Fall Indicator
- Can be supplied with Stainless Steel Cable and Stainless Steel Swivel Snap Hook on Request

Materials


- Polymer Casing
- 4.5mm Galvanised Steel Wire - MBS 15kN
- Galvanised ANSI Steel Snap Hook - MBS 23kN
- Galvanised ANSI Steel Karabiner - MBS 23kN

How To Use

- Refer to User Instruction Manual


IT IS EASY TO SHIFT TO WINCH MODE FROM BLOCK MODE (AND VICE VERSA) FOLLOWING THE BELOW STEPS

BLOCK MODE
Enables easy movement of the user while working in confined space



Pull the pin and push the handle to reverse in Block mode

WINCH MODE
Enables easy retrieval of the victim post fall arrest



Pull the pin and handle to shift to Winch Mode



AFS510020R
Length: 20m
Weight: 8.1kg



AFS510030R
Length: 30m
Weight: 14.6kg