SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

현장을 이해하고, 필요한 솔루션을 연결합니다.

산업안전 · 추락방지 시스템
산업용 소재 · 건축자재
제품 제안부터 공급·시공·설치·교육까지



COMPANY INFORMATION

스냅슛 (SNAPSHOOT)

ADDRESS (15431) 경기도 안산시 단원구 풍전로 37-9 트리플렉스 301동 118호
TEL 0507-1374-9229
FAX 0504-481-6749
E-MAIL bkkim@snapshoot.co.kr

TECHNICAL DOCUMENTS

인증서 · 데이터시트 · 기술자료

제품의 규격과 성능, 인증 및 적용 조건을 확인하기 위한 자료입니다.

ABOUT SNAPSHOOT

제품 공급을 넘어, 현장에 맞는 해결책으로

스냅슛은 산업현장의 작업 환경과 요구 조건을 바탕으로
적합한 제품과 시스템을 제안합니다. 현장 실사를 통해 설치 조건을 확인하고,
공급부터 시공·설치 및 사용 교육까지 필요한 과정을 함께합니다.

추락방지 시스템

안전대부착설비 · 수평·수직 라이프라인
레일 시스템 · 리지드 포스트

밀폐공간 진입·구조 솔루션

데빗암 · 삼각대 · 구조용 윈치
윈치 안전블록 · 구조장비

산업안전 보호구

전신형 안전대 · 랜야드 · 안전블록
작업 환경에 맞춘 개인보호구

산업용 소재·건축자재

산업용 테이프 · 접착제 · 기능성 소재
구조용 스크류 · 목조건축 자재

SNAPSHOOT
ENGINEERED FOR A SAFER TOMORROW

홈페이지 바로가기 →
문서 라이브러리 바로가기 →
시공사례 바로가기 →
문의하기 →

본 페이지는 스냅슛의 자료 제공 안내용 표지입니다. 첨부된 인증서 및 기술자료의 발행 주체, 인증 대상과 적용 범위는 해당 원문을 기준으로 확인해 주세요.

KSTRONG WRANGLER 25M ADJUSTABLE HORIZONTAL LIFELINE 4 MAN SYSTEM

AFA940010

Features

- Light Weight quick and easy to install, reusable Horizontal lifeline system.
- 4 Steel O-Rings to enable the user to easily attach the Lanyard of his Harness to the Lifeline using a Connector.
- Has 2 Cross Arm Straps each to tie off to the structure where the anchorage is required.
- Has unique tension indicator for creating an adequate tension in the line. Once the required tension is achieved, the disc on the tension indicator rotates freely, indicating the line is ready to use.
- Has Swivel Connector- specially designed to prevent any twisting of the rope.
- Supplied with 2 x 1.5m Anchor straps AFA920015(1.5M)
- Suitable for upto 4 users

25M. ADJUSTABLE WRANGLER™
4-PERSON TEMPORARY HORIZONTAL LIFELINE

How To Use

Refer to User Instruction Manual

SCAN TO DOWNLOAD

Material

Rope Line	:	16 mm Kernmantle Rope, MBS 40kN
Tensioner	:	Aluminum Alloy & Stainless Steel
O Rings	:	Forged Alloy Steel
	:	MBS 23kN
Karabiners	:	Galvanized Steel
	:	MBS 40kN
Cross Arm Strap	:	Polyester 44mm, MBS 25kN



System Strength and Span

Minimum Breaking Strength: 25kN

Minimum Span: 5m

Maximum Span: 25m



AFA920015(1.5M)

Weight

9.28 kgs ± 0.10 kgs

Relevant Standards

EN 795:2012 TYPE C & TS 16415:2013 TYPE C

